

Durapipe VKD Double Union Ball Valve

Description: In-line double union ball valve with lockable handle

Mounting: In any position

Maximum Fluid Pressure at 20°C: 16 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C


Seals: FPM

Seats: PTFE

End Connections: Solvent Sockets

Features: Safe blocked unions, multi-functional handle, easy actuator mounting platform and bracketing points included

Options: Electric or pneumatic actuation



MM Solvent Cement Sockets

FPM Seals	16	H0 DKK 305	66.65
PTFE Seals	20	H0 DKK 306	66.95
	25	H0 DKK 307	88.13
	32	H0 DKK 308	103.89
	40	H0 DKK 309	105.83
	50	H0 DKK 310	145.26
	63	H0 DKK 311	198.17
	75	H0 DKK 312	542.86
	90	H0 DKK 313	667.53
	110	H0 DKK 314	810.39

Praher Type S4 Ball Valve

Description: In-line double union ball valve with lockable handle

Mounting: In any position

Maximum Fluid Pressure at 20°C: Sizes 20mm-63mm 16 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: PVC-C

Seals: EPDM or FPM

Seats: PTFE

End Connections: Solvent Sockets

Features: Lockable handle and tagging point included



MM Solvent Cement Sockets

EPDM Seals	20	12.8448	43.03
PTFE Seals	25	12.8468	50.53
	32	12.8472	63.08
	40	12.8476	80.99
	50	12.8480	96.15
	63	12.8484	122.21

MM Solvent Cement Sockets

FPM Seals	20	12.8449	48.14
PTFE Seals	25	12.8469	66.09
	32	12.8473	81.80
	40	12.8477	103.55
	50	12.8481	122.30
	63	12.8485	146.40

Durapipe TKD 3-Way T-Port Ball Valve

Description: In-line horizontal T-port 3-way ball valve with lockable handle

Mounting: In any position

Maximum Fluid Pressure at 20°C: 16 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C

Seals: FPM

Seats: PTFE

End Connections: Solvent Sockets

Features: Safe blocked unions, multi-functional handle and easy actuator mounting platform

Options: L-Port; electric or pneumatic actuation



MM Solvent Cement Sockets

FPM Seals	20	H0 TTK 306	147.63
PTFE Seats	25	H0 TTK 307	162.94
	32	H0 TTK 308	195.70
	40	H0 TTK 309	246.10
	50	H0 TTK 310	288.92
	63	H0 TTK 311	360.18

Durapipe VM Diaphragm Valve

Description: In-line diaphragm valve with position indicator

Mounting: In any position

Maximum Fluid Pressure at 20°C: 10 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C

Diaphragm: FPM

End Connections: Solvent Sockets up to 63mm - Solvent Spigots 75, 90 & 110mm

Options: EPDM or PTFE diaphragm; pneumatic actuation



MM Solvent Cement Unions

FPM Diaphragm	20	H0 UMK 306	235.13
	25	H0 UMK 307	255.72
	32	H0 UMK 308	274.23
	40	H0 UMK 309	368.17
	50	H0 UMK 310	419.01
	63	H0 UMK 311	583.84

MM Solvent Cement Spigots

FPM Diaphragm	75	H0 VMK 412	668.51
	90	H0 VMK 413	753.47
	110	H0 VMK 414	1022.77



Actuated Valves

Durapipe PVC-C ball valves, butterfly valves and diaphragm valves are also available actuated. Please enquire for prices and information.

Durapipe FK Butterfly Valve

Description: Wafer style butterfly valve

Mounting: In any position, between flanges to BS 4504 PN10, BS 10 Table D/E or ANSI 150

Maximum Fluid Pressure at 20°C: Sizes 50mm to 63mm - 16 bar; sizes 75mm to 160mm - 10 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: PPGR (Polypropylene glass reinforced)

Disc: PVC-C

Seals: EPDM or FPM

End Connections: Flange mounted (flanges not included)

Options: Lug body for end of line use; FPM seals; pneumatic actuation



Lever Operated

EPDM Seals

50	H0 FKJ 106	196.19
63	H0 FKJ 107	206.95
75	H0 FKJ 108	224.28
90	H0 FKJ 109	249.35
110	H0 FKJ 110	298.01
160	H0 FKJ 112	467.66

To order FPM seals, change code to FKK (prices on request)

Need advice on actuation?

Contact Tony Welsh

Call our freephone:

0800 975 79 71

Or from outside of the UK:

+44 191 521 3111



Durapipe SR Single Union Ball Check Valve

Description: In-line ball check valve

Mounting: Vertical

Maximum Fluid Pressure at 20°C: 16 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C

Seals: EPDM or FPM

End Connections: Male solvent spigot x female solvent union

Options: EPDM seals



MM Solvent Spigot x Socket

FPM Seals	Size	Code	Price
	20	H0 SRK 306	61.70
	25	H0 SRK 307	68.51
	32	H0 SRK 308	89.51
	40	H0 SRK 309	130.59
	50	H0 SRK 310	136.27
	63	H0 SRK 311	164.49

To order EPDM seals, change code from SRK to SRJ



SR Check Valve Installation

Note that this valve must be installed at a minimum distance of 10 x nominal diameter (eg. 20" for size 2") from pump flange.

Durapipe RV Y-Type Strainer

Description: In-line sediment strainer

Mounting: In any position

Maximum Fluid Pressure at 20°C: 16 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C

Seals: EPDM or FPM

Strainer: Stainless Steel with 0.7mm mesh

End Connections: Solvent Sockets



MM Solvent Cement Sockets

FPM Seals	Size	Code	Price
	20	H0 UVK 306	111.78
	25	H0 UVK 307	128.26
	32	H0 UVK 308	156.68
	40	H0 UVK 309	206.14
	50	H0 UVK 310	296.85
	63	H0 UVK 311	327.99